



**Dejavoo**  **Systems**

**Z11**



**Z8**



**DEPENDABLE**

Global market leader in secured contact and contactless payment. RoHS, CE, FCC & BSMI certified. Tested to perform even under extreme conditions.



**ADAPTABLE**

Offering the full range of payment, communications and connectivity options. Up to 4 SAM slots, expansive memory for multi-app support. Ergonomic compact design fits any working space. Cost efficient, Linux open architecture OS allows flexibility in the integration of business applications.



**SECURED**

PCI PTS, EMV L1 L2, Visa payWave, MasterCard PayPass, American Express, & JCB J/ Speedy certified.



**INTUITIVE**

3.5 touch screen or 2.4 color LCD screen with in-built contactless reader enriches user experience. Large backlit keypad and LCD screen provides ease of pin entry in all lighting conditions.



<b>ZLine Countertop Series</b>		<b>Z11 Touch</b>	<b>Z8 Dual Comm</b>	
<b>Processor</b>		32 bits high performance secure Microprocessor, @ 400MHz		
<b>Memory</b>	Flash/ DDR RAM	128 MB/ 64 MB (Up to 256 MB/ 128 MB)		
	Micro-SD Socket	⊙		
<b>Display</b>		3.5" color TFT-LCD 320x480 pixels	2.4" color TFT-LCD 320x240 pixels	
<b>Capacitive Touch Screen</b>		⊙	X	
<b>Card Reader</b>	Magnetic Strip	ISO 7810, 7811 & 7813 Triple track, Bi-Directional		
	Contact	User Card	ISO 7816 ID-1 1.8V/3V/5V T=0, T=1	
	Card	SAM Card (up to 4)	2	2
	Contactless (Optional)	ISO 14443 Type A, B, ISO 18092 NFC and Mifare® & SONY® Felica Working frequency 13.56MHz		
	Dual SIM	⊙	⊙	
<b>Communications Interface (Optional)</b>	Communications	UMTS, GPRS, CDMA, WiFi, Bluetooth		
	Connectivity	Ethernet, DiaUp Modem, 2x RS232, 2xUSB		
<b>Indicator</b>	LED- 4 LEDs	X	⊙	
	Audio- Buzzer	⊙	⊙	
<b>Keypad</b>	Standard Keys	15	15	
	Function Keys	X	6	
<b>Power Supply</b>		9V/ 4A		
<b>Dimensions (L/W/H)</b>		190 mm x 78 mm x 78 mm		
<b>Weight</b>		350g	375g	
<b>Printer With Graphical Capabilities</b>		57 mm x 50 mm, 100 mm/ sec		
<b>Environment</b>	Operating Temperature	0 °C to 50 °C		
	Storage Temperature	-20 °C to 70 °C		
	Operating Humidity	5% to 90% non-condensing		
	Storage Humidity	5% to 95% non-condensing		
<b>Certifications</b>	Security& Payment	PCI PTS, EMV L1 L2, TQM, PBOC L1 L2 Visa payWave, MasterCard PayPass, American Express, & JCB J/ Speedy		
	Safety, EMC	CE, FCC, BSMI, RoHS		
<b>Software</b>		SDK, KMS, TMS, Simulator, CTOS library, ISO 8583 library, Crypto library		
<b>Crypto</b>		TRNG, DES, T'DES, AES, RSA, MK/SK, DUKPT, T'DES DUKPT		

\*\*Product technical specifications are subject to change. For latest information, visit <http://www.dejavoo.com>

Dejavoo Systems  
1129 Northern Blvd Suite 303  
Manhasset NY, 11030 USA  
+1-877-358-6797

[www.dejavoo.com](http://www.dejavoo.com)

**Dejavoo**  **Systems**

